

View Online at <https://aerobasegroup.com/nsn/5930-01-226-0460>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

0.575 inches

**Body Width:**

0.535 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.690 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.740 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary, two positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Test Data Document:**

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret

**Specification Data:**

96906-ms27718 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0