

View Online at <https://aerobasegroup.com/nsn/5930-01-226-1699>

**Overall Length:**

2.905 inches

**Overall Height:**

4.312 inches

**Overall Width:**

1.937 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.436 inches

**Longest Vertical Distance Between Mounting Centers:**

1.436 inches

**End Application:**

Model ms496

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base and threaded hole

**Cubic Measure:**

864.000 cubic inches

**Thready Qty Per Inch (tpi):**

24 single pressure connection

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

5.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+10.00 to 230.00 actuation point pounds per square inch and +11.00 to 250.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point serrated nut and external deactuation point serrated nut

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Special Features:**

Used on 210 ft u. S. Coast guard vessels

**Frequency In Hertz:**

60.0 third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0