

View Online at <https://aerobasegroup.com/nsn/5930-01-226-1699>

Overall Length:

2.905 inches

Overall Height:

4.312 inches

Overall Width:

1.937 inches

Longest Horizontal Distance Between Mounting Centers:

1.436 inches

Longest Vertical Distance Between Mounting Centers:

1.436 inches

End Application:

Model ms496

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Cubic Measure:

864.000 cubic inches

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+10.00 to 230.00 actuation point pounds per square inch and +11.00 to 250.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point serrated nut and external deactuation point serrated nut

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Special Features:

Used on 210 ft u. S. Coast guard vessels

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0