NSN 5930-01-226-2032

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-226-2032

Overall Length: 0.740 inches Overall Height: 3.060 inches Overall Width: 0.740 inches Body Length: 0.740 inches Body Length: 0.740 inches Body Width: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Uniterial Style: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel							
Overall Height: 3.060 inches Overall Width: 0.740 inches Body Length: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.540 inches Actuator Width: 0.550 inches Actuator Width: 0.750 inches Actuator Width: 0.750 inches Actuator Uidth: 0.750 inches Actuator Uidth: 0.750 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Mount Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
3.060 inches Overall Width: 0.740 inches Body Length: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Overall Width: 0.740 inches Body Length: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
0.740 inches Body Length: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Body Length: 0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Uidth: 0.740 inches Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
0.740 inches Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Body Width: 0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
0.740 inches Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Body Height: 1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
1.450 inches Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Actuator Length: 0.740 inches Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
O.740 inches Actuator Style: Rectangular Actuator Width: O.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Actuator Style: Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Rectangular Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Actuator Width: 0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
0.740 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
White single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Illuminated Actuator Color: White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
White single actuator Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Actuator Inscription: Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Manual stop single actuator Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Maximum Voltage Rating In Volts: 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
250.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:							
Inclosure Type: Fully enclosed Mounting Method:							
Fully enclosed Mounting Method:							
Mounting Method:							
-							
Panel							
Features Provided:							
Rfi shielding							
Nonpile-up Contact Arrangement:							
2 pole, double throw, one position momentary single switch unit							
Contact Load Current Rating At Maximum Rated Voltage:							
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac							
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac							
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac Terminal Type And Quantity:							
Terminal Type And Quantity:							

NSN 5930-01-226-2032

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0