

View Online at <https://aerobasegroup.com/nsn/5930-01-226-2901>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.531 inches

Flat Height:

0.219 inches all actuators

Shaft Diameter:

0.250 inches all actuators

Shaft Length:

0.500 inches all actuators

Overall Diameter:

2.187 inches

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 5: 00 o'clock

End Application:

6525-01-159-3009 field radiographic/fluoroscopic x-ray system; model dxd 350 ii

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Threaded stud single mounting facility

Features Provided:

Variable resistor provisions

Cubic Measure:

16.889 cubic inches

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

11 all actuators

Shaft Type:

Round, flatted all actuators

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Special Features:

Tandem switch assembled with resistors mounted on tabs

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Purchase Description Identification:

24456-46-178080g1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0