Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-3655

Hazardous Locations/environmental Protection:	
Shock proof	
Overall Length:	
3.520 inches	
Overall Height:	
1.740 inches	
Overall Width:	
2.500 inches	
Unthreaded Mounting Hole Diameter:	
0.189 inches single mounting facility	
Individual Section Quantity:	
1	
Longest Horizontal Distance Between Mounting Centers:	
1.620 inches single mounting facility	
Longest Vertical Distance Between Mounting Centers:	
1.250 inches single mounting facility	
Switch Contact Basic Design:	
Nonpile-up nonsymmetrical	
Mounting Method:	
Bracket single mounting facility and unthreaded hole single mounting facility	
Features Provided:	
Actuator knob and legend plate	
Contact Voltage Rating In Volts:	
440.0 highest ac voltage rating at sea level	
Mounting Facility Pattern:	
Four position rectangular single mounting facility	
Switch Actuator Indexing Position Quantity:	
3 single actuator	
Terminal Type:	
Tab w/screw	
Switch Actuator Positioning Increment:	
90.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Fixed stop single actuator	
Contact Load Current Rating:	
750.0 milliamperes resistive load highest ac voltage rating at sea level	
Special Features:	
Legend plate reads purify clean standby	
Style Designator:	
Tap, circuit selector	
Shelf Life:	
N/a	

NSN 5930-01-226-3655 Rotary Switch - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0

