

View Online at <https://aerobasegroup.com/nsn/5930-01-226-3656>

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Length:**

3.520 inches

**Overall Height:**

1.740 inches

**Overall Width:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.189 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.620 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.250 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

750.0 milliamperes resistive load highest ac voltage rating at sea level

**Special Features:**

Legend plate reads normal high

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0