# NSN 5930-01-226-3666

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-226-3666



#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Corrosion resistant

#### **Overall Length:**

0.750 inches

#### **Overall Height:**

3.050 inches

#### **Overall Width:**

0.750 inches

#### **Body Length:**

0.688 inches

#### **Body Width:**

0.750 inches

#### Case Material:

Metal

## Actuator Length:

0.620 inches

## Actuator Style:

### Rectangular

Actuator Height:

#### 0.150 inches

Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

Auto-2 manual-2 single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### Features Provided:

Rfi shielding

#### Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

# NSN 5930-01-226-3666

Push Switch - Page 2 of 2



## Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0