NSN 5930-01-226-3669

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-3669
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.750 inches
Overall Height:
3.050 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
$7.000 \ amperes \ resistive \ dc \ and \ 4.000 \ amperes \ inductive \ dc \ and \ 2.500 \ amperes \ lamp \ dc \ and \ 7.000 \ amperes \ resistive \ ac \ and \ 7.000 \ amperes \ and \ and \ 7.000 \ amperes \ and \ and \ 7.000 \ amperes \ and \ a$

Terminal Type And Quantity:

inductive ac and 2.000 amperes lamp ac

6 turret and 5 tab, solder lug

NSN 5930-01-226-3669

Push Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0