NSN 5930-01-226-3669

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-226-3669 |
|--|
| Body Style: |
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 0.750 inches |
| Overall Height: |
| 3.050 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.150 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Rfi shielding |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| $7.000 \ amperes \ resistive \ dc \ and \ 4.000 \ amperes \ inductive \ dc \ and \ 2.500 \ amperes \ lamp \ dc \ and \ 7.000 \ amperes \ resistive \ ac \ and \ 7.000 \ amperes \ and \ and \ 7.000 \ amperes \ and \ and \ 7.000 \ amperes \ and \ a$ |

Terminal Type And Quantity:

inductive ac and 2.000 amperes lamp ac

6 turret and 5 tab, solder lug

NSN 5930-01-226-3669

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0