NSN 5930-01-226-3670

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-3670
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.750 inches
Overall Height:
3.050 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Push to test-3 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

Terminal Type And Quantity:

inductive ac and 2.000 amperes lamp ac

12 turret and 5 tab, solder lug

NSN 5930-01-226-3670

Push Switch - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0