## NSN 5930-01-226-5547

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-5547

Overall Length:
1.187 inches
Overall Height:
0.437 inches
Body Diameter:
0.625 inches
Body Height:
0.187 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.938 inches
End Application:
6530-01-134-3182 thermoregulator, patient
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Cubic Measure:
0.700 cubic inches
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Two position in-line  Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action Terminal Type: Quick disconnect, male
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:  8.0 amperes resistive load single voltage
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action Terminal Type: Quick disconnect, male Contact Load Current Rating: 8.0 amperes resistive load single voltage Contact Adjustability:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:  8.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point not adjustable
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action Terminal Type: Quick disconnect, male Contact Load Current Rating: 8.0 amperes resistive load single voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:  8.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point not adjustable  Contact Stimulus Rating:  48.50 actuation point degrees celsius
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:  8.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point not adjustable  Contact Stimulus Rating:  48.50 actuation point degrees celsius  Contact Voltage Rating In Volts:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Quick disconnect, male  Contact Load Current Rating:  8.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point not adjustable  Contact Stimulus Rating:  48.50 actuation point degrees celsius  Contact Voltage Rating In Volts:  110.0 ac at sea level single voltage
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type: Quick disconnect, male  Contact Load Current Rating: 8.0 amperes resistive load single voltage  Contact Adjustability: Actuation point not adjustable  Contact Stimulus Rating: 48.50 actuation point degrees celsius  Contact Voltage Rating In Volts:  110.0 ac at sea level single voltage  Special Features:
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action Terminal Type: Quick disconnect, male Contact Load Current Rating: 8.0 amperes resistive load single voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 48.50 actuation point degrees celsius Contact Voltage Rating In Volts: 110.0 ac at sea level single voltage Special Features: Color coded, blue dot
Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action Terminal Type: Quick disconnect, male Contact Load Current Rating: 8.0 amperes resistive load single voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 48.50 actuation point degrees celsius Contact Voltage Rating In Volts: 110.0 ac at sea level single voltage Special Features: Color coded, blue dot Frequency In Hertz:

## NSN 5930-01-226-5547

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc w/flange
Purchase Description Identification:
3095-87-737-0000
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A048b0