NSN 5930-01-226-5992

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-5992
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.750 inches
Overall Height:
3.050 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Actuator Inscription:
Command-3 data-3 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-01-226-5992

Push Switch - Page 2 of 2



Special	Features:
---------	-----------

Horizontal split lens

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0