NSN 5930-01-226-7760

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-7760

View Online at https://aerobasegroup.com/nsn/5930-01-226-7760
Thread Class:
2a single threaded bushing
Hazardous Locations/environmental Protection:
Moisture resistant and salt spray resistant and vibration proof
Overall Length:
0.373 inches
Body Length:
0.170 inches
Tempurature Sensing Element Type:
Internal sensor
Width Across Flats:
0.281 inches
Operating Tempurature Rating:
Between -80.0 degrees fahrenheit and 400.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
1.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
205.00 actuation point degrees fahrenheit and 175.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Style Designator:

Plug

NSN 5930-01-226-7760

Thermostatic Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0