

View Online at <https://aerobasegroup.com/nsn/5930-01-226-7763>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

2.245 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.162 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Rfi shielding

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Shaft and wave washer surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0