# NSN 5930-01-226-7769

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-7769

#### **Hazardous Locations/environmental Protection:**

Explosion proof and moisture resistant

**Overall Length:** 

2.410 inches

**Overall Height:** 

2.760 inches

**Overall Width:** 

1.920 inches

#### **Unthreaded Mounting Hole Diameter:**

0.140 inches single mounting facility

#### **Individual Section Quantity:**

2

#### **Longest Horizontal Distance Between Mounting Centers:**

2.146 inches single mounting facility

#### **Longest Vertical Distance Between Mounting Centers:**

1.200 inches single mounting facility

# **Mounting Method:**

Bracket and unthreaded hole single mounting facility

# **Actuator Type:**

Thumbwheel all actuators

# **Features Provided:**

Illuminated and rfi shielding

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# **Mounting Facility Pattern:**

Four position rectangular single mounting facility

# **Switch Actuator Indexing Position Quantity:**

10 all actuators

#### **Terminal Type:**

Printed circuit

# **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

# **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

# **Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions each section

#### Color:

White each indicator marking

# **Style Designator:**

Rectangular inline indicating

#### Shelf Life:

N/a

# NSN 5930-01-226-7769

Code Indicating Wheel Switch - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A052b0