# NSN 5930-01-226-8404

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-8404

## **Thread Class:**

2b all threaded hole

# Hazardous Locations/environmental Protection:

Vibration proof

# **Overall Length:**

3.062 inches

## **Body Diameter:**

0.500 inches

#### **Body Length:**

2.750 inches

# **Overall Diameter:**

0.500 inches

## **Distance Between Mounting Facility Centers:**

0.750 inches

## **Tempurature Sensing Element Type:**

Internal sensor

# Mounting Method:

Bracket and threaded hole

# Thready Qty Per Inch (tpi):

32 all threaded hole

# **Contact Action Stimulus:**

Increase

# Thread Size:

0.138 inches all threaded hole

# Mounting Facility Pattern:

Two position in-line

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

## **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

5.0 amperes resistive load first voltage

## **Contact Adjustability:**

Actuation point not adjustable

## **Contact Stimulus Rating:**

130.00 actuation point degrees fahrenheit

# **Contact Voltage Rating In Volts:**

32.0 dc at sea level second voltage

# Media For Which Designed:

Gas or liquid

#### Style Designator:

Cylindrical

# NSN 5930-01-226-8404

Thermostatic Switch - Page 2 of 2

# **Thread Series Designator:**

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

