NSN 5930-01-226-9594

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-226-9594

| Thread Class: |
|---|
| 2a single threaded stud |
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Overall Height: |
| 1.111 inches |
| Body Height: |
| Between 0.400 inches and 0.451 inches |
| Overall Diameter: |
| 0.625 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Threaded stud |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.190 inches single threaded stud |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 6.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 333.00 actuation point degrees fahrenheit and 365.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level second voltage |
| Media For Which Designed: |
| Gas or liquid |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Diag |
| Disc |

Unf single threaded stud

NSN 5930-01-226-9594

Thermostatic Switch - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0