

View Online at <https://aerobasegroup.com/nsn/5930-01-226-9978>

**Thread Class:**

2a single threaded stud

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

Between 2.812 inches and 4.906 inches

**Overall Height:**

1.531 inches

**Overall Width:**

1.250 inches

**Body Length:**

2.000 inches

**Operating Temperature Rating:**

55.0 degrees celsius

**Mounting Method:**

Threaded stud

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.190 inches single threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

720.00 actuation point feet per minute and 4000.00 actuation point feet per minute and 105.00 differential point feet per minute and 320.00 differential point feet per minute

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0