

View Online at <https://aerobasegroup.com/nsn/5930-01-226-9978>

Thread Class:

2a single threaded stud

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 2.812 inches and 4.906 inches

Overall Height:

1.531 inches

Overall Width:

1.250 inches

Body Length:

2.000 inches

Operating Temperature Rating:

55.0 degrees celsius

Mounting Method:

Threaded stud

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

720.00 actuation point feet per minute and 4000.00 actuation point feet per minute and 105.00 differential point feet per minute and 320.00 differential point feet per minute

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Unf single threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0