

View Online at <https://aerobasegroup.com/nsn/5930-01-227-5724>

Hazardous Locations/environmental Protection:

Weathertight

Overall Length:

8.740 inches

Overall Height:

2.440 inches

Overall Width:

4.470 inches

Body Length:

3.880 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

4.500 inches

Longest Vertical Distance Between Mounting Centers:

2.375 inches

Pressure Switch Type:

Differential

Mounting Method:

Flange and unthreaded hole

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches all pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+2.50/+8.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut with scale

Contact Stimulus Rating:

4.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Special Features:

Altered iaw dwg 5547957 for spst normally open operation

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0