

View Online at <https://aerobasegroup.com/nsn/5930-01-227-5724>

**Hazardous Locations/environmental Protection:**

Weathertight

**Overall Length:**

8.740 inches

**Overall Height:**

2.440 inches

**Overall Width:**

4.470 inches

**Body Length:**

3.880 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches

**Longest Vertical Distance Between Mounting Centers:**

2.375 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Flange and unthreaded hole

**Thready Qty Per Inch (tpi):**

18 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1000.00 pounds per square inch

**Thread Size:**

0.250 inches all pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+2.50/+8.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut with scale

**Contact Stimulus Rating:**

4.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

480.0 ac at sea level single voltage

**Special Features:**

Altered iaw dwg 5547957 for spst normally open operation

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0