## NSN 5930-01-227-7549

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-227-7549

**Thread Class:** 

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

**Overall Length:** 

2.312 inches

**Overall Height:** 

1.750 inches

**Overall Width:** 

1.750 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.813 inches single actuator

**Nonturn Device Radius:** 

0.500 inches at 12: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 12: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 single section front

**Throw Quantity:** 

5 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-01-227-7549

Rotary Switch - Page 2 of 2



Cc	nta	ct S	witcl	hina	Actic	'n.
v	nıta	UL O	WILL	ши	Actic	" .

Makes before breaks single section front

**Switch Actuator Positioning Increment:** 

15.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0