NSN 5930-01-227-8261

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-227-8261

Overall Length:
4.938 inches
Overall Height:
2.875 inches
Overall Width:
2.875 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.0 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube
Capillary tube Operating Tempurature Rating:
Operating Tempurature Rating:
Operating Tempurature Rating: 185.0 degrees fahrenheit
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method:
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided:
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus:
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern:
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement:
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Operating Tempurature Rating: 185.0 degrees fahrenheit Mounting Method: Bracket and unthreaded hole Features Provided: Electrical access port Contact Action Stimulus: Increase Mounting Facility Pattern: Isosceles triangle Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:

+25.00 to 90.00 actuation point degrees fahrenheit Contact Adjustment Type:

Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:

External actuation point screw

NSN 5930-01-227-8261

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level eighth voltage Frequency In Hertz: 60.0 third voltage Media For Which Designed: Gas Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A048b0