NSN 5930-01-227-8263

Thermostatic Switch - Page 1 of 1

A048b0



| View Online at https://aerobasegroup.com/nsn/5930-01-227-8263 |
|---|
| Hazardous Locations/environmental Protection: |
| Vibration resistant and humidity resistant |
| Overall Height: |
| 0.250 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| Between -40.0 degrees fahrenheit and 350.0 degrees fahrenheit |
| Contact Action Stimulus: |
| Increase |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Contact Load Current Rating: |
| 5.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 125.00 actuation point degrees fahrenheit and 115.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 240.0 ac at sea level second voltage |
| Frequency In Hertz: |
| 60.0 second voltage |
| Media For Which Designed: |
| Gas or liquid |
| Precious Material And Location: |
| Contact silver |
| Precious Material: |
| Silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |