NSN 5930-01-228-0683

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-228-0683
Overall Length:
7.850 inches
Overall Height:
2.910 inches
Overall Width:
2.810 inches
Individual Section Quantity:
6
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
End Application:
6115-01-143-3850 generator, alternating current
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section periphery
Throw Quantity:
8 each section periphery
Mounting Method:
Bracket single mounting facility
Features Provided:
Legend plate and actuator knob
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

NSN 5930-01-228-0683

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0