

View Online at <https://aerobasegroup.com/nsn/5930-01-228-5538>

**Thread Length:**

0.414 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Fungus resistant and humidity resistant and shock resistant and vibration resistant

**Overall Length:**

1.525 inches

**Overall Height:**

1.349 inches

**Overall Width:**

1.200 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.206 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.586 inches single actuator

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

5.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Detent Rotational Torque Range:**

+1.000/+2.000 inch-pounds single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load ac at sea level

**Contact Arrangement Truth Table:**

Special single section

**Special Truth Table Identification:**

53711-special 0-1-2-3-4 single section

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular panel mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0