

View Online at <https://aerobasegroup.com/nsn/5930-01-228-5538>

Thread Length:

0.414 inches single mounting facility

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and shock resistant and vibration resistant

Overall Length:

1.525 inches

Overall Height:

1.349 inches

Overall Width:

1.200 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.206 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.586 inches single actuator

Individual Section Quantity:

1

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

5.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+2.000 inch-pounds single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Contact Arrangement Truth Table:

Special single section

Special Truth Table Identification:

53711-special 0-1-2-3-4 single section

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular panel mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0