NSN 5930-01-228-5540

Lock Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-228-5540

Thread Class:
2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
2.130 inches
Overall Height:
1.575 inches
Overall Width:
1.575 inches
Body Diameter:
1.170 inches
Bushing Length:
0.522 inches
Body Length:
1.280 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
1.375 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac
Precious Material And Location:
Contact surfaces silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-228-5540

Lock Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0