NSN 5930-01-228-6909

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-228-6909

view Online at https://derobasegroup.com/nsi//0550-01-220-0505
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Dustproof and explosion proof
Overall Length:
0.890 inches
Overall Height:
1.985 inches
Overall Width:
0.890 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
1.885 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.095 inches and 0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Anal single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-228-6909

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0