## NSN 5930-01-228-8713

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-228-8713

| Hazardous Locations/environmental Protection:           |
|---|
| Corrosion resistant and vibration resistant             |
| Overall Length:   |
| 1.590 inches  |
| Body Length:  |
| 0.700 inches  |
| Overall Diameter:                                       |
| 0.250 inches  |
| Tempurature Sensing Element Type:                       |
| Internal sensor   |
| Mounting Method:  |
| Clamp   |
| Contact Action Stimulus:                                |
| Increase  |
| Nonpile-up Contact Arrangement:                         |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type:  |
| Wire lead   |
| Contact Load Current Rating:                            |
| 1.0 amperes resistive load second voltage               |
| Contact Adjustability:                                  |
| Actuation point not adjustable                          |
| Contact Stimulus Rating:                                |
| 10.00 actuation point degrees celsius                   |
| Contact Voltage Rating In Volts:                        |
| 120.0 ac at sea level first voltage                     |
| Media For Which Designed:                               |
| Liquid or semisolid                                     |
| Style Designator:                                       |
| Cylindrical   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:                                       |
| No  |
| Fiig:   |
| A048b0  |