## NSN 5930-01-228-9787

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-228-9787

Panel mounted  Overall Length:  1.985 inches  Overall Height: 0.890 inches  Overall Width: 0.890 inches  Body Length: 1.885 inches  Body Width: 0.750 inches  Body Height: 0.750 inches  Case Material: Metal  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	
Overall Length:  1.985 inches Overall Height:  0.890 inches Overall Width:  0.890 inches Body Length:  1.885 inches Body Width:  0.750 inches Body Height:  0.750 inches Case Material: Metal Actuator Length:  0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width:  0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Body Style:
1.985 inches  Overall Height: 0.890 inches  Overall Width: 0.890 inches  Body Length: 1.885 inches  Body Width: 0.750 inches  Body Height: 0.750 inches  Case Material: Metal  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	Panel mounted
Overall Height:  0.890 inches Overall Width:  0.890 inches Body Length:  1.885 inches Body Width:  0.750 inches Body Height:  0.750 inches Case Material: Metal Actuator Length:  0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width:  0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Overall Length:
Overall Width:  0.890 inches  Body Length:  1.885 inches  Body Width:  0.750 inches  Body Height:  0.750 inches  Case Material:  Metal  Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  Between 0.095 inches and 0.100 inches  Actuator Width:  0.620 inches  Actuator Color:  Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	1.985 inches
Overall Width:  0.890 inches  Body Length:  1.885 inches  Body Width:  0.750 inches  Body Height:  0.750 inches  Case Material:  Metal  Actuator Length:  0.620 inches  Actuator Style:  Rectangular  Actuator Height:  Between 0.095 inches and 0.100 inches  Actuator Width:  0.620 inches  Actuator Color:  Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	Overall Height:
0.890 inches Body Length: 1.885 inches Body Width: 0.750 inches Body Height: 0.750 inches Case Material: Metal Actuator Length: 0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	0.890 inches
Body Length:  1.885 inches Body Width:  0.750 inches Body Height:  0.750 inches Case Material: Metal Actuator Length:  0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Overall Width:
1.885 inches Body Width: 0.750 inches Body Height: 0.750 inches Case Material: Metal Actuator Length: 0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	0.890 inches
Body Width:  0.750 inches  Body Height:  0.750 inches  Case Material: Metal  Actuator Length:  0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width:  0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	Body Length:
0.750 inches  Body Height: 0.750 inches  Case Material: Metal  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	1.885 inches
Body Height: 0.750 inches Case Material: Metal Actuator Length: 0.620 inches Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Body Width:
O.750 inches  Case Material:  Metal  Actuator Length: O.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: O.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	0.750 inches
Case Material:  Metal  Actuator Length: 0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed  Mounting Method: Panel Features Provided:	Body Height:
Metal  Actuator Length:  0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width:  0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	0.750 inches
Actuator Length:  0.620 inches  Actuator Style: Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width:  0.620 inches  Actuator Color: Black single actuator  Illuminated Actuator Color: White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	Case Material:
Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Metal
Actuator Style: Rectangular Actuator Height: Between 0.095 inches and 0.100 inches Actuator Width: 0.620 inches Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Actuator Length:
Rectangular  Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed  Mounting Method: Panel Features Provided:	0.620 inches
Actuator Height: Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Actuator Style:
Between 0.095 inches and 0.100 inches  Actuator Width: 0.620 inches  Actuator Color:  Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	Rectangular
Actuator Width:  0.620 inches  Actuator Color:  Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	Actuator Height:
O.620 inches  Actuator Color:  Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	Between 0.095 inches and 0.100 inches
Actuator Color: Black single actuator Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Actuator Width:
Black single actuator  Illuminated Actuator Color:  White single actuator  Actuator Inscription:  Alert inhibit single actuator  Maximum Voltage Rating In Volts:  28.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Panel  Features Provided:	0.620 inches
Illuminated Actuator Color: White single actuator Actuator Inscription: Alert inhibit single actuator Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Actuator Color:
White single actuator  Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed  Mounting Method: Panel  Features Provided:	Black single actuator
Actuator Inscription: Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Illuminated Actuator Color:
Alert inhibit single actuator  Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	White single actuator
Maximum Voltage Rating In Volts:  28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Actuator Inscription:
28.0 dc Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Alert inhibit single actuator
Inclosure Type: Fully enclosed Mounting Method: Panel Features Provided:	Maximum Voltage Rating In Volts:
Fully enclosed  Mounting Method:  Panel  Features Provided:	28.0 dc
Mounting Method: Panel Features Provided:	Inclosure Type:
Panel Features Provided:	Fully enclosed
Features Provided:	Mounting Method:
	Panel
Full display long and actuator soal	Features Provided:
Full display letts and actuator seal	Full display lens and actuator seal
Nonpile-up Contact Arrangement:	Nonpile-up Contact Arrangement:
	1 pole, double throw, one position momentary single switch unit
1 note double throw one position momentary single switch unit	i polo, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## NSN 5930-01-228-9787

Push Switch - Page 2 of 2



Precious	Material	<b>And</b>	Location:

Contacts gold

**Terminal Type And Quantity:** 

3 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0