NSN 5930-01-229-0663

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-229-0663

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

3.260 inches

Overall Height:

1.770 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.095 inches and 0.105 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

3.080 inches and 3.090 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.960 inches and 0.970 inches single mounting facility

Operating Tempurature Range:

-65.0 to 85.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Turret and printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 2nd section

Contact Arrangement Truth Table:

Special, 2 pole - 2 positions 3rd section

Color:

White each indicator marking

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

NSN 5930-01-229-0663

Code Indicating Wheel Switch - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A052b0