

View Online at <https://aerobasegroup.com/nsn/5930-01-229-0770>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof and moisture resistant

Overall Length:

1.925 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

2.334 inches

Overall Width:

0.688 inches

Bushing Length:

0.609 inches

Body Length:

1.925 inches

Body Width:

0.688 inches

Body Height:

0.922 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.990 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

480.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0