

View Online at <https://aerobasegroup.com/nsn/5930-01-229-2949>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Length:**

1.000 inches

**Body Width:**

1.000 inches

**Body Height:**

2.600 inches

**Case Material:**

Metal

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Both pa pp single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Countermeasures set an/alq-141

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:**

Contact surfaces silver

**Terminal Type And Quantity:**

17 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0