## NSN 5930-01-229-2960

Push Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-01-229-2960
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Body Length:
1.000 inches
Body Width:
1.000 inches
Body Height:
2.600 inches
Case Material:
Metal
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Fm upper single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Countermeasures set an/alq-141
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes
inductive ac and 2.000 amperes lamp ac
Precious Material And Location:
Contact surfaces silver
Terminal Type And Quantity:
17 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5930-01-229-2960

Push Switch - Page 2 of 2



Fiig:

A053a0