NSN 5930-01-229-2965

Push Switch - Page 1 of 2

Between 0.950 inches and 0.970 inches

Between 0.950 inches and 0.970 inches

Body Style:
Panel mounted
Overall Length:
3.320 inches
Overall Height:
1.210 inches
Overall Width:

Body Width:

Body Height:



View Online at https://aerobasegroup.com/nsn/5930-01-229-2965

1.200 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.050 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.720 inches and 0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Form feed single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.812 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding and full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

NSN 5930-01-229-2965

Push Switch - Page 2 of 2



Pr	ecious	Material	And	Location:
----	--------	----------	-----	-----------

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0