NSN 5930-01-229-2968



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-229-2968 **Body Style:** Panel mount **Hazardous Locations/environmental Protection:** Explosion proof **Body Length:** 1.000 inches **Body Width:** 1.000 inches **Body Height:** 2.600 inches **Case Material:** Metal **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Actuator Inscription:** Ech0 repeat single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** Countermeasures set an/alq-141 **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Features Provided:** Rfi shielding **Nonpile-up Contact Arrangement:** 3 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac **Precious Material And Location:** Contact surfaces silver **Terminal Type And Quantity:** 17 tab, solder lug Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5930-01-229-2968

Push Switch - Page 2 of 2



Fiig:

A053a0