## NSN 5930-01-229-7236

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-229-7236

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof

**Overall Length:** 

1.765 inches

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.750 inches single actuator

**Overall Diameter:** 

0.500 inches

**Individual Section Quantity:** 

1

**Operating Tempurature Range:** 

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

**Throw Quantity:** 

4 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round single actuator

Terminal Type:

Printed circuit

**Contact Switching Action:** 

Makes before breaks single section rear

**Switch Actuator Positioning Increment:** 

36.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-01-229-7236

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

200.0 milliamperes resistive load ac at sea level

**Style Designator:** 

Snap or line

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0