

View Online at <https://aerobasegroup.com/nsn/5930-01-229-7249>

Body Style:

Bushing mounted

Overall Length:

1.794 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Body Diameter:

0.500 inches

Bushing Length:

0.266 inches

Body Length:

0.984 inches

Case Material:

Metal

Actuator Diameter:

0.303 inches

Actuator Height:

0.344 inches

Actuator Color:

Natural single actuator

Illuminated Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

End Application:

6625-01-068-6694 oscilloscope; sturgeon class ssn (637), ticonderoga class cg (47), los angeles class ssn (688), virginia class cgn (41), oliver perry class ffg, spruance class dd (963), kidd class ddg, nimitz class cvn, Forrestal class cv, austin ship class lpd-4 amphibious transport docks

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

0.100 amperes resistive dc and 0.100 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces silver and contacts and terminal surfaces gold

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0