## NSN 5930-01-229-9358

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-229-9358

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof

Body Length:

1.000 inches

## Body Width:

1.000 inches

#### **Body Height:**

2.600 inches

**Case Material:** 

Metal

Actuator Color:

#### White single actuator

**Illuminated Actuator Color:** 

## White single actuator

**Actuator Inscription:** 

Active single actuator

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### End Application:

Countermeasures set an/alq-141

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Rfi shielding

#### Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

#### **Precious Material And Location:**

Contact surfaces silver

#### **Terminal Type And Quantity:**

17 tab, solder lug

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5930-01-229-9358

Push Switch - Page 2 of 2

Fiig: A053a0

