NSN 5930-01-229-9359

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-229-9359

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Length:

1.000 inches

Body Width:

1.000 inches

Body Height:

2.600 inches

Case Material:

Metal

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Fm lower single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Countermeasures set an/alq-141

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-229-9359

Push Switch - Page 2 of 2

Fiig: A053a0

