NSN 5930-01-230-2814

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mount

Waterproof
Overall Length:
0.740 inches
Overall Height:
3.000 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches



View Online at https://aerobasegroup.com/nsn/5930-01-230-2814

Body Width:
0.740 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator and black single actuator
Illuminated Actuator Color:
Green single actuator and amber single actuator
Actuator Inscription:
Pulse unavail, square wave (symbol) single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator green, lower half of actuator amber
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
End Application:
Missile guidance and tracking set an/spg-55b
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac
Precious Material And Location:
Contact surfaces gold

NSN 5930-01-230-2814

Push Switch - Page 2 of 2



Terminal Type And Quantity:	
17 pin	
Shelf Life:	
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0