

View Online at <https://aerobasegroup.com/nsn/5930-01-230-2814>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

0.740 inches

**Overall Height:**

3.000 inches

**Overall Width:**

0.740 inches

**Body Length:**

0.740 inches

**Body Width:**

0.740 inches

**Actuator Length:**

0.740 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.740 inches

**Actuator Color:**

White single actuator and black single actuator

**Illuminated Actuator Color:**

Green single actuator and amber single actuator

**Actuator Inscription:**

Pulse unavail, square wave (symbol) single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator green, lower half of actuator amber

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Missile guidance and tracking set an/spg-55b

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Contact surfaces gold

**Terminal Type And Quantity:**

17 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0