# NSN 5930-01-230-2814

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-2814

#### **Body Style:**

Panel mount

### Hazardous Locations/environmental Protection:

Waterproof

## **Overall Length:**

0.740 inches

#### **Overall Height:**

3.000 inches

### **Overall Width:**

0.740 inches

#### **Body Length:**

0.740 inches

#### **Body Width:**

0.740 inches

#### Actuator Length:

## 0.740 inches

Actuator Style:

Rectangular

## Actuator Width:

0.740 inches

## Actuator Color:

White single actuator and black single actuator

## Illuminated Actuator Color:

Green single actuator and amber single actuator

#### **Actuator Inscription:**

Pulse unavail, square wave (symbol) single actuator

### Illuminated Actuator Color Sequence:

Upper half of actuator green, lower half of actuator amber

### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### **End Application:**

Missile guidance and tracking set an/spg-55b

### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

### Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

 $5.000 \mbox{ amperes resistive dc}$  and  $2.500 \mbox{ amperes inductive dc}$  and  $5.000 \mbox{ amperes resistive ac}$ 

## **Precious Material And Location:**

Contact surfaces gold

# NSN 5930-01-230-2814

Push Switch - Page 2 of 2

Terminal Type And Quantity:

17 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

