

View Online at <https://aerobasegroup.com/nsn/5930-01-230-2815>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

0.740 inches

Overall Height:

3.000 inches

Overall Width:

0.740 inches

Body Length:

0.740 inches

Body Width:

0.740 inches

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Width:

0.740 inches

Actuator Color:

White single actuator and black single actuator

Illuminated Actuator Color:

White single actuator and amber single actuator

Actuator Inscription:

Doppler unavail, sinewave (symbol) single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator white, lower half of actuator amber

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Missile guidance and tracking set an/spg-55b

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

17 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0