NSN 5930-01-230-2942

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-2942

| Body Style: |
|---|
| Hole mount |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant |
| Overall Length: |
| 1.050 inches |
| Overall Height: |
| 0.700 inches |
| Overall Width: |
| 0.700 inches |
| Body Diameter: |
| 0.600 inches |
| Body Length: |
| 0.625 inches |
| Actuator Style: |
| Round, stepped |
| Actuator Diameter: |
| 0.700 inches |
| Actuator Height: |
| 0.300 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained and center position maintained and left position maintained and right position |
| maintained |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| 4920-01-179-8469 adapter, test |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 four way single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes inductive dc |
| Test Data Document: |
| 81349-mil-s-9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

5 tab, solder lug

Specification Data:

81349-mil-s-9419/2 government specification

Shelf Life:

NI/a

NSN 5930-01-230-2942 Toggle Switch - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A053a0