

View Online at <https://aerobasegroup.com/nsn/5930-01-230-2945>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

2.610 inches

Overall Height:

0.940 inches

Overall Width:

0.890 inches

Bushing Length:

0.620 inches

Body Length:

0.940 inches

Body Width:

0.660 inches

Body Height:

1.170 inches

Actuator Length:

0.730 inches

Actuator Style:

Rectangular

Actuator Height:

0.840 inches

Actuator Width:

0.730 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 turret

Specification Data:

81349-mil-s-22885/81 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0