NSN 5930-01-230-3067

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-3067

| Overall Length: |
|---|
| 3.500 inches |
| Overall Height: |
| 3.700 inches |
| Overall Width: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches |
| Capillary Tube Length: |
| 48.0 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.500 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 1.750 inches |
| End Application: |
| 6530-01-134-3182 thermoregulator, patient |
| Tempurature Sensing Element Type: |
| Capillary tube |
| Mounting Method: |
| Unthreaded hole |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Four position rectangular |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 24.0 amperes motor load single voltage |
| Contact Adjustability: |
| Actuation point adjustable, preset and deactuation point adjustable, preset |
| Contact Adjustment Range: |
| +0.00 to 55.00 actuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External actuation point shaft |
| Contact Stimulus Rating: |
| 12.00 differential point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 120.0 ac at sea level single voltage |
| Media For Which Designed: |
| Liquid |
| |

NSN 5930-01-230-3067

Thermostatic Switch - Page 2 of 2

Style Designator:

Rectangular

Purchase Description Identification:

3095-87-738-5000

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0

