NSN 5930-01-230-5323

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-230-5323

Overall Length:
2.844 inches
Overall Height:
1.500 inches
Overall Width:
0.656 inches
Body Length:
2.156 inches
Body Width:
0.625 inches
Body Height:
Between 0.510 inches and 0.520 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
2.437 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -100.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mary Con Black and
Mounting Method:
Bracket and unthreaded hole
•
Bracket and unthreaded hole
Bracket and unthreaded hole Contact Action Stimulus:
Bracket and unthreaded hole Contact Action Stimulus: Increase
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage Contact Adjustability:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range:
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +50.00 to 300.00 actuation point degrees fahrenheit
Bracket and unthreaded hole Contact Action Stimulus: Increase Mounting Facility Pattern: Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Threaded stud Contact Load Current Rating: 5.0 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable, preset Contact Adjustment Range: +50.00 to 300.00 actuation point degrees fahrenheit Contact Adjustment Type:

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

NSN 5930-01-230-5323

Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
60.0 second voltage
Media For Which Designed:
Gas
Style Designator:
Rectangular w/bracket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0